



BAG EMPTIER DUST EXTRACTOR



Capacity to: 1800 m³/h on 800 Pa

Material: Epoxy resin dualcomponent/ RAL7032

Weight: 105Kg

Warranty: 1 year

SPECIFICATIONS

WORKING PRINCIPLE

Allow to open the bags in a controlled environment. Vacuuming or removing dispersed dust when the chemicals are attached on the volumetric dosificator. Equipped with a 0,55 KW motor, to stoke 590 g of dust, rated with a grade IP54. The emptier is connected with a flange at the bottom improving the stability. The dust are retired with a set of filters.

APPLICATION

Enable to empty bins and bags, in a safe, efficient and dust-free manner. This is good for the health of operators and the environment. Dust problems caused by emptying bags of fine, aerated or volatile powders. This ensures that a healthy environment is maintained in the process area as well as reducing maintenance and repair problems caused by powder contamination to surrounding machinery, in the industries.

FEATURES

Leakproof

Feeding closed

Significantly reduced dust emissions

Improved operator efficiency

Cleaner working environment

Motor	0,55 kW, 120/220 V, 60 Hz, IP54 Iso-cl.-F, available upon request for another version
Filtres	EU 4 S – 1/1
Extration index	95%
Dimensions(L/W/H)	1300mm/800mm/1280 mm